



Thermafloor UNDERTILE HEATING KIT

Contents of this kit includes

- Deluxe touchscreen thermostat
- Heating cable element
- Cable Testing Alarm
- Floor Probe
- High Tack spray adhesive
- Adhesive tape
- Installation Manual and Thermostat instructions



Price and Sizing Guide

150 watts 0.6m ² - 1.0 m ²		900 watts 5.6m ² - 6.3 m ²	
200 watts 1.0m ² - 1.5 m ²		1000 watts 6.3m ² - 7.0 m ²	
300 watts 1.5m ² - 2.2 m ²		1250 watts 7.0m ² - 8.5 m ²	
400 watts 2.2m ² - 3.0 m ²		1500 watts 8.5m ² - 10.0 m ²	
500 watts 3.0m ² - 3.6 m ²		1800 watts 10.0m ² - 12.5 m ²	
600 watts 3.6m ² - 4.2 m ²		2000 watts 12.5m ² - 14.5 m ²	
700 watts 4.2m ² - 5.0 m ²		2500 watts 14.5m ² - 17.5 m ²	
800 watts 5.0m ² - 5.6 m ²		3000 watts 17.5m ² - 22 m ²	



Technical Specifications

STANDARD	IEC 60800:2009
Cable Construction	Single Conductor with a screen
Rated Voltage	230V
Output	11.5w/m
Cable Diameter	2.5 mm
Conductor Insulator	Fluor-Polymer (imported from Solway)
Outer insulation	PVC
Maximum Ambient Temperature	85°F (30°C)
Minimum Installation Temperature	40°F (5°C)
Cold lead	Two wires plus ground braid both measuring 2.5m length

